

2012 EPIC (26" / 29er)



BEARING KIT PART # 9891-5250				SPECIFICATION					
ITEM #	LOCATION	PART	QTY		MODEL	Ø OD	Ø ID	WIDTH	
1-A	Bottom Bracket	Bearing	3	Steel	6801V-2RS	21	12	5	
1-B		Sleeve	1	Aluminum		15	12.2	32.5	
1-C		O-ring	2	Rubber		16.8	11.8	2.5	
1-D	Dropout	Bearing	4	Steel	6800-2RS	19	10	5	
1-E		Spacer (Outer)	4	Aluminum		18	10.1	1.5	Chamfer
1-F		Spacer (Inner)	2	Aluminum		16.5	10.1	4	Chamfer x 2
1-G	S-Link @ Seat Tube	Bearing	2	Steel	688-2RS	16	8	5	
1-H		Spacer	2	Aluminum		14	8	2	Chamfer
1-I	S-Link @ Seatstay	Bearing	2	Steel	688-2RS	16	8	5	
1-J		Spacer	4	Aluminum		14	8	2	Chamfer

SPECIALIZED BICYCLE COMPONENTS
 15130 Concord Circle, Morgan Hill, CA 95037
 (408) 779-6229
 SC0401 Rev.A, December 2011
 Please note all instructions are subject to change for improvement without notice.
 Please visit www.specialized.com for periodic tech updates.
 Feedback: techdocs@specialized.com

NOTE: Apply blue threadlocker to all threads

BOLT KIT PART # 9891-5255				SPECIFICATION									
ITEM #	LOCATION	PART	QTY		Ø OD	Ø ID	WIDTH	THREAD	mm		mm		
2-A	Bottom Bracket	Axle	1	Aluminum				12	66	Chamfer	5	Allen Hex	160 - 180
2-B		Axle washer	1	Steel	15.4	12.5	0.7						
2-C		Axle cone	1	Aluminum	20	12	10.5						
2-D		Axle o-ring	1	Rubber	14	10	2						
2-E		Axle cone o-ring	1	Rubber	18.6	13.8	2.4						
2-F	Dropout	Bolt	2	Aluminum				10	29.5		4	Allen Hex	120 - 140
2-G		Washer	2	Steel	17	10.2	0.3						
2-H	S-Link @ Seat Tube	Bolt	1	Aluminum				8	53		4	Allen Hex	120 - 140
2-I		Nut	1	Aluminum	15.7			8	4.5		11	6pt Socket	
2-J	S-Link @ Seatstay	Bolt	2	Aluminum				8	18		4	Allen Hex	70 - 90
2-K		Washer	2	Steel	13.8	8.1	0.3						
2-L	Lower Shock Eye	Bolt	1	Steel				6	42		5	Allen Hex	60 - 70
2-M		Washer	1	Steel	10	6.2	0.5						
2-N	Upper Shock Eye	Bolt (Alloy frame)	1	Aluminum				8	26.5		4	Allen Hex	70 - 90
2-N		Bolt (Carbon frame)	1	Aluminum				8	32.5		4	Allen Hex	70 - 90
2-O		Washer	1	Steel	16	8.1	0.2						

SCHEMATIC #35

