



www.c-bear.com

info@c-bear.com

+32 (0)11 603 208

A = ATB/MTB  
AC = MTB-Cyclocross  
C = Cyclocross  
R = Race



Facebook/  
cBearCeramicBottomBracket

Instagram : cbearcycling



**C-Bear Bottom Bracket Chart**

**Step 1**

**Step 2**

**Step 3**

		Threaded			BB386	BBRight Cervelo	OSBB 61 (carbon) Specialized	Pressfit30 (PF30)	PF30A Cannondale	BB30A Cannondale	BB30	PressFit (BB86/BB92)	T47	BB90/95 Trek
		BSA Road	BSA MTB	ITA										
BB shell ID mm					46	46	46	46	46	42	42	41		37
BB shell WIDTH mm		68	68	70	86.5(Road)	79(Road)	61(Road)	68(Road)	73(Road)	73(Road)	68(Road)	86.5(Road)	68(Road)	90(Road)
Crankset								73(MTB)			73(MTB)	92(MTB)	73(MTB)	95(MTB)
Spindle diameter 24 mm	Shimano HTII Race Face X-Type Rotor 3D, Agilis, Rex3	 BSA-ROAD-R BSA-ROAD-C	 BSA-MTB	 ITA-R ITA-C	 BB386-24-R BB386-24-C	 BBR24-R BBR24-C	 OSBB61-24-R OSBB61-24-C	 PF30-24-R PF30-24-AC	 PF30A-24-R PF30A-24-C	 BB30A-24-R BB30A-24-C	 BB30-24-R BB30-24-AC	 PF41-R PF41-AC	 T47-24-68-R T47-24-68-C T47-24-73-A	 BB90/95-24-R BB90/95-24-AC
	FSA Mega Exo	 BSA-ROAD-FSA-R BSA-ROAD-FSA-C	 BSA-MTB	 ITA-R ITA-C	 BB386-24-R BB386-24-C	 BBR24-R BBR24-C	 OSBB61-24-R OSBB61-24-C	 PF30-24-R PF30-24-AC	 PF30A-24-R PF30A-24-C	 BB30A-24-R BB30A-24-C	 BB30-24-R BB30-24-AC	 PF41-R PF41-AC	 T47-24-68-R T47-24-68-C T47-24-73-A	
Spindle diameter 24-22 mm	SRAM / Truvativ GXP	 BSA-GXP-R BSA-GXP-C	 BSA-GXP-A	 ITA-GXP-R ITA-GXP-C	 BB386-GXP-R BB386-GXP-C	 BBR-CXP-R BBR-CXP-C	 OSBB61-GXP-R OSBB61-GXP-C	 PF30-GXP-R PF30-GXP-AC	 PF30A-GXP-R PF30A-GXP-C	 BB30A-GXP-R BB30A-GXP-C	 BB30-GXP-R BB30-GXP-AC	 PF41-GXP-R PF41-GXP-AC	 T47-CXP-68-R T47-CXP-68-C T47-CXP-73-A	 BB90/95-GXP-R BB90/95-GXP-AC
Spindle diameter 25 mm	Campagnolo UT/ PT	 BSA-CAM-UT-R BSA-CAM-UT-C BSA-CAM-PT-R BSA-CAM-PT-C		 ITA-CAM-UT-R ITA-CAM-UT-C ITA-CAM-PT-R ITA-CAM-PT-C	 BB386-CAM-UT-R BB386-CAM-UT-C BB386-CAM-PT-R BB386-CAM-PT-C	 BBR-CAM-UT-R BBR-CAM-UT-C	 OSBB61-CAM-R OSBB61-CAM-C	 PF30-CAM-UT-R PF30-CAM-UT-C PF30-CAM-PT-R PF30-CAM-PT-C			 BB30-CAM-UT-R BB30-CAM-UT-C BB30-CAM-PT-R BB30-CAM-PT-C	 PF41-CAM-UT-R PF41-CAM-UT-C PF41-CAM-PT-R PF41-CAM-PT-C		
Spindle diameter 30 mm	Campagnolo OT FSA EVO386 THM Clavicula ZIPP Vumaquad	 BSA386-R BSA386-AC	 BSA386-AC		 BB386-R BB386-C	 BBR386-R BBR386-C	 OSBB61-86-R OSBB61-86-C	 PF30-386-R PF30-386-AC			 BB30-386-R BB30-386-AC	 PF41-30-R PF41-30-AC	 T47-30-68-R T47-30-68-C T47-30-73-A	
	Rotor : 3D+, 3DF Rex 1/ Rex 2 Aldhu SRAM Quarq Dzero Easton EC90 Hope FSA EVO392	 BSA30-R BSA30-AC	 BSA30-AC	 ITA30R	 BB386-R BB386-C	 BBR86-R BBR86-C <small>(not suitable for rotor oem crank)</small>	 OSBB61-86-R OSBB61-86-C	 PF30-86-R PF30-86-AC	 PF30A-86-R		 BB30-86-R BB30-86-AC	 PF41-30-R PF41-30-AC	 T47-30-68-R T47-30-68-C T47-30-73-A	
	FSA BB30, SRAM BB30 Cannondale Hollowgram						 OSBB61-8830-R OSBB61-8830-C	 PF30-R PF30-AC	 PF30A-R PF30A-C	 PF42-30-R PF42-30-C	 PF42-30-R PF42-30-AC		 T47-8830-R	
	Specialized - Fact						 OSBB61-FACT-R OSBB61-FACT-C	 OSBB61-FACT-R OSBB61-FACT-C			 PF42-30-R PF42-30-AC			
Spindle diameter 29.88 mm	DUB	 DUB-BSA					 DUB PF30				 DUB 8830	 DUB PF41		

Copyright © c-bear®. All Rights Reserved.

**Pulleys**  
Shimano /Sram/ Campagnolo  
HC = hybrid ceramic  
FC = full ceramic

Aluminum	Carbon (dry, road only)	Delrin	Titanium	sram XX1	Sram Eagle
↓	↓	↓	↓	↓ (delrin only)	↓ (alum. Only)
PULL ALU SHI/SRAM	PULL CAR SHI/SRAM	PULL DEL SHI/SRAM	PULL TIT SHI/SRAM	PULL DEL XX1	PULL ALU EAGLE
PULL ALU SHI/SRAM FC		PULL DEL SHI/SRAM FC	PULL TIT SHI/SRAM FC		
PULL ALU CAM		PULL DEL CAM	PULL TIT CAM		
PULL ALU CAM FC		PULL DEL CAM FC	PULL TIT CAM FC		

**Wheel bearings**

Too many to list. Please provide bearing code or dimension and quantity